



Type SSV

Strip Soffit Ventilator

- Regulation airflow compliance
- Integral fly screening
- Accepts different soffit thicknesses
- Self coloured - corrosion proof


| | |
|----------------------------|---|
| PRODUCT NAME | Type SSV Strip Soffit Ventilator |
| SIZE | 2400 x 50 x 20mm |
| FREE AIRFLOW RATING | 10,000mm ² per running metre pitches above 15° |
| COLOURS | White Brown Black |
| MATERIAL | PVCU |
| OBSERVATIONS | Predrilled fixing holes |

USE

Permits entry of air via soffit.

SOLUTION

The Type SSV Strip Soffit Ventilator is designed for use with a standard soffit board. It permits airflow via the soffit area whilst also providing support for soffit boards from 4mm to 14mm thickness. The airflow rating is 10,800mm² per metre run, making it suitable for use where the roof pitch is 15 degrees or above.



The ventilation slots provide screening in accordance with regulations. (See Type SSV-15 for higher airflow rating.)

SPECIFICATION WORDING

Type SSV Strip Soffit Ventilator by Cavity Trays of Yeovil Somerset BA22 8HU (01935 474769) Colour..... Clip to soffit and secure to fascia. Metres run.....

Type SSV-RU Strip Soffit Ventilator with Reduced Upstand by Cavity Trays of Yeovil Somerset BA22 8HU (01935 474769) Colour..... Slot into soffit and secure to fascia. Metres run.....

Type SSV-RU

Strip Soffit Ventilator with reduced upstand

- Regulation airflow compliance
- Integral fly screening
- Accepts different soffit thicknesses
- Self coloured - corrosion proof

| | |
|----------------------------|---|
| PRODUCT NAME | Type SSV-RU Strip Soffit Ventilator with Reduced Upstand |
| SIZE | 2400 x 50 x 5mm |
| FREE AIRFLOW RATING | 10,000mm ² per running metre pitches above 15° |
| COLOURS | White Brown |
| MATERIAL | PVCU |
| OBSERVATIONS | Fits groove in most fascia backs |


USE

Permits entry of air via soffit.

SOLUTION

The Type SSV-RU Strip Soffit Ventilator is designed for use with a standard soffit board. The RU designation refers to a reduced upstand of 5mm.

This permits the Type SSV-RU to be fitted into the back location groove of a fascia.



All other details and dimensions are as per the standard Type SSV. The airflow rating is 10,800mm² per metre run, making it suitable for use where the roof pitch is 15 degrees or above. The ventilation slots provide screening in accordance with regulations.

SPECIFICATION WORDING

Type SV-FL Flat Soffit Strip by Cavity Trays of Yeovil Somerset BA22 8HU (01935 474769) Colour..... Secure to soffit and fascia. Metres run.....